



NYLON CAP SPEC SHEET

FYRELANE USA

Fyrelane USA Nylon Caps



- Material: Dupont Zytel
- Tensile Strength: 12,900 psi
- Elongation: 5.4%
- Flexural Modulus: 13,500 psi
- Deflection Temp: 233c @ 264psi
- Specific Gravity: 1.19 gram/cubic cm
- Operating PSI: up to 250 psi
- Operating Temperature: -200F to +260F
- UV Protection: Zytel and Color Additives

THE PART NUMBERS LISTED ARE NATIONAL STANDARD THREADS ONLY

<u>Part Numbers</u>	<u>Descriptions</u>
HSPC-2.5NH-COLOR-ASSY	2 ½"Nst Nylon cap with gasket only
HSPC-2.5NH-COLOR-LOOP-ASSY	2 ½" Nst Nylon cap with loop, cable and gasket
HSPC-4.0NH-COLOR-ASSY	4.0" Nst Nylon cap with gasket only
HSPC-4.0NH-COLOR-LOOP-ASSY	4.0" Nst Nylon cap with loop, cable and gasket
HSPC-4.5NH-COLOR-ASSY	4 ½"Nst Nylon cap with gasket only
HSPC-4.5NH-COLOR-LOOP-ASSY	4 ½" Nst Nylon cap with loop, cable and gasket

Offered Colors by sizes:

Colors Available in 2 ½" are (Blue, Green, Orange, Purple, Red, Yellow)

Colors Available in 4" are (Green, Orange, Red, Yellow)

Colors Available in 4 ½" (Blue, Green, Orange, Purple, Red, Yellow)

Note: Other colors available not listed, but require minimum order of 250 units each size. Sizes cannot be mixed

OTHER VARIOUS INFORMATION

Various Information	<p>Fyrelane USA Nylon Caps are manufactured from Dupont Zytel Material with extra additives to induce the strength. The Caps are manufactured to remain intact up to 250 psi water Pressure and are static pressured up to 450 psi. If hit with Hammer or stressed with a pipe wrench, the cap will spring back to its original shape.</p> <p>Nylon caps have no scrap value, nor will it rust or corrode. Does not require painting or lubrication to operate.</p>
Sole Source Contact Info	<p>Fyrelane USA 8701 John Carpenter Frwy, Suite 230 Dallas, Texas Toll Free: 1-855-359-9555 Fax: 972-594-7826 Email: Sales@fyrelaneusa.com</p>